



**NOTES:**

- 1. MATERIALS:**  
 FRAME - STEEL, NICKEL PLATED  
 SPRINGS - SPRING TEMPERED, NICKEL SILVER  
 BUSHING & SHAFT - BRASS, NICKEL PLATED  
 INSULATION - PHENOLIC  
 CONTACTS - FINE SILVER  
 SCREWS - STEEL, NICKEL PLATED  
 SHAFT INSULATOR - NYLON  
 TUBING - THERMOPLASTIC  
 KNURLED NUT - BRASS, NICKEL PLATED
- 2. ELECTRICAL CHARACTERISTICS:**  
 - CONTACT RESISTANCE: 20 MILLIOHMS MAX  
 - CONTACT RATING: 3A, 300W MAX AC NON-INDUCTIVE LOAD  
 - LEAKAGE RESISTANCE: 1000 MEGAOHMS OR GREATER  
 - DIELECTRIC STRENGTH: 250 VDC
- 3. HARDWARE SHIPPED UNASSEMBLED.**
- 4. THIS PRODUCT IS RoHS COMPLIANT.**

**CUSTOMER DRAWING**

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					UNLESS OTHERWISE SPECIFIED			MATERIAL SPEC No.	
					1. ALL DIMENSIONS IN INCHES [mm]				
					- TWO PLACE DECIMALS ±0.02 [0.5]				
					- THREE PLACE DECIMALS ±0.005 [0.13]			SHEET 1 OF 1	
B	28121	12/11/18	PC	TJK	FINISH	DATE DRAWN	BY	CHKD	APVD
A	26166	10/18/06	PC	TJK	SPEC No.	3/16/10	RS	RS	TJK
REV	ECO NUMBER	DATE	BY	APVD	FIRST USED ON	SCALE 2:1		PART No.	
REVISIONS					DO NOT SCALE DRAWING				
					NAME RIGHT-ANGLE LEVER SWITCH, 3 POSITION LOCKING, RoHS				
					12012X				
					REV B				